

Node Specifications

1. Node String

1A. 150mm  
1B. 300mm

Lp1  
\*Default length is 200mm  
\*Minimum spacing is 80mm

Lp2 (Quantity)  
\*Due to handling maximum of 15 meter in length

2A. 150mm  
2B. 300mm

Input side M16 Male

Output side M16 Female

2. Node & Cabling color

3. Color/ CCT

4. Control

5. Connector, Bare wire

6. Node Model

7. Node Cover

Node String

Reference	1	2	Lp1 (mm)	Lp2 (Quantity)	Quantity of Node strings
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			
	A B	A B			

Node Specifications

2	3	4	5	6	7
A B		A B	A B	A B	A B C D
A B	A B	A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B	A B	A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B	A B	A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B	A B	A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B	A B	A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D
A B	A B	A B	A B	A B	A B C D
A B		A B	A B	A B	A B C D

Cabling Specifications

8. M16 3Pin Leader Cable (Short Range)

A. 1 m  
B. 2 m  
C. 3 m

9. M16 3Pin Jumper Cable (Short Range)

A. 1 m  
B. 2 m  
C. 3 m

10. M16 3Pin Power Cable (Short Range)

11. M12 3Pin Leader Cable (Long Range)

A. 15 m  
B. 25 m  
C. 50 m  
D. Custom

12. M16 3Pin Power Cable (Long Range)

Accessories

13. Mounting Clip

14. M16 End cap

15. Mounting Profile  
\*Default length of 2000mm  
\*Default spacing of 200mm  
\*Custom on request

16. Panel ring

Cabling

Nr.	Option	Length (m)	Quantity
8	A B C	-	
9	A B C	-	
10	-	-	
11	A B C D	-	
12	-	-	

Accessories

Nr.	Quantity
13	
14	
15	
16	