


DiGi Neonflex Side Bend Multi Color RGBW 48V

181

The DiGi Neonflex Side Bend Multi Color RGBW 48V is a flexible linear lighting solution for clean, continuous lines of dynamic RGBW lighting in architectural applications. With side-bend flexibility, it smoothly navigates tight curves, circular forms, and contours.

Ideal for curved facades, circular features, and artistic installations requiring lateral bending. The DiGi Neonflex Side Bend Multi Color RGBW is perfect for dynamic lighting schemes with high-quality RGBW lighting.

- Application-Driven Format – Multiple shapes and sizes enable seamless integration into both compact and large-scale architectural elements.
- Precise Dynamic Effects – From subtle fades to sweeping movement, pixel-controlled white lighting brings dynamic expression to static tones.



Specifications

General

| | |
|-------------------------|----------------------|
| Power Consumption (W/m) | 20 |
| Input Voltage (V DC) | 48 |
| LEDs (/m) | 84 |
| LED Pitch (mm) | 11,9 |
| LEDs (/segment) | 14 |
| Pixels (/m) | 6 |
| Channels (/m) | 24 |
| Beam Angle (°) | 1121, 1616, 2222 120 |
| | 1128 270 |
| LED Type | 4in1 |
| Color Range | RGBW |
| CRI | ≥80, ≥90 |
| Control | DMX |

Installation Conditions & Lighting Data

| | |
|--|-------------------|
| Segment Length (mm) | 167 |
| Bending Radius (mm) | 1121, 1128 80 |
| | 1616 150 |
| | 2222 400 |
| Maximum Run Length Power ¹ (m) | Single Feed 20 |
| | Double Feed 40 |
| Maximum Run Length Data ¹ (m) | @30fps 85 |
| | @45fps 57 |
| Maximum Leader Cable Length ¹ (m) | Up to 20 |
| Lumen Maintenance Calculated | L70 @ 25°C 70,000 |
| Hours (h) | L70 @ 50°C 50,000 |

¹More details can be found in the Installation Guide document.

Operating

| | |
|-------------------------------|-----------------------------|
| Environment | Outdoor |
| Installation Temperature (°C) | 0 to +50 |
| Working Temperature (°C) | -40 to +55 |
| Saltwater Resistant | Yes |
| UV Resistant | Yes |
| Flame Resistant | Yes |
| IK Rating | IK08 |
| IP Rating | IP68 |
| Certification | CE, RoHS, UL, UKCA, CB, FCC |
| Limited Warranty | 5 Years |

Physical

| | |
|---------------------|------------------|
| Housing Material | Silicone |
| Cable Material | Silicone |
| Connector Material | Nylon (PA66) |
| Housing Color | White |
| Connector Type | Bare Wires / M12 |
| Weight (kg/m) | 1121, 1616 0,45 |
| | 1128 0,55 |
| | 2222 0,6 |
| Dimensions WxH (mm) | 1121 11,5 x 21 |
| | 1616 16,5 x 16,5 |
| | 1128 11,5 x 28 |
| | 2222 22,4 x 22,6 |

Options

Color/CCT


- RGBW2700K
- RGBW3000K
- RGBW4000K
- RGBW5000K

Lighting Specifications


DiGi Neonflex Side Bend

| | Full RGBW (lm/m) | Red (lm/m) | Green (lm/m) | Blue (lm/m) | White (lm/m) |
|------------------------|---------------------|---------------|-----------------|----------------|-----------------|
| 1121 48V RGBW2700K DMX | | | | | |
| 1121 48V RGBW3000K DMX | | | | | |
| 1121 48V RGBW4000K DMX | | | | | |
| 1121 48V RGBW5000K DMX | | | | | |
| 1616 48V RGBW2700K DMX | | | | | |
| 1616 48V RGBW3000K DMX | | | | | |
| 1616 48V RGBW4000K DMX | | | | | |
| 1616 48V RGBW5000K DMX | | | | | |
| 1128 48V RGBW2700K DMX | | | | | |
| 1128 48V RGBW3000K DMX | | | | | |
| 1128 48V RGBW4000K DMX | | | | | |
| 1128 48V RGBW5000K DMX | | | | | |
| 2222 48V RGBW2700K DMX | | | | | |
| 2222 48V RGBW3000K DMX | | | | | |
| 2222 48V RGBW4000K DMX | | | | | |
| 2222 48V RGBW5000K DMX | | | | | |


Photometric Distribution



1121 - 111.9° Average Beam Angle




1616 - 113.1° Average Beam Angle




1128 - 167.6° Average Beam Angle

Dimensions




Accessory Options




1121 / 1128¹

- ____ Straight Profile
- ____ Clip Profile²
- ____ Straight Profile Cable Duct
- ____ Straight Profile Transparent
- ____ Curved Profile



1616¹

- ____ Straight Profile
- ____ Clip Profile²
- ____ Straight Profile Cable Duct
- ____ Straight Profile Recessed
- ____ Straight Profile Transparent
- ____ Curved Profile
- ____ Curved Profile Cable Duct
- ____ Recessed Profile End Cap



2222¹


- ____ Straight Profile
- ____ Clip Profile²
- ____ Straight Profile Cable Duct
- ____ Curved Profile

¹ Straight Profile is shown. The dimensions shown are not to scale. Please refer to the Dimensions Sheet document for additional dimensions.
² Straight installation has only 4 pieces per meter, while curved installation has 8 pieces per meter.


Profile Specifications

Physical


| | |
|------------------------------|---------------------|
| Profile Material | Aluminum Alloy 6063 |
| Transparent Profile Material | Polycarbonate |
| Aluminum Profile Finish | Blank Anodized |




Straight Cable Duct



Recessed Transparent Flex




Clip Profile



Straight Profile¹


¹ 1000mm profile is standard. 2000mm is available to order.

Cable Entry Options




Connection Options


DMX Bare Wires with waterstop¹



M12 Male Connector³



M12 Female Connector



Wire Color

| | |
|--------|---------|
| Red | 48 V+ |
| Green | Data + |
| Yellow | Data - |
| White | Program |
| Black | GND |

Connector Pin

| | | |
|-------|--------|---------|
| Pin 1 | Red | 48 V+ |
| Pin 2 | Green | Data + |
| Pin 3 | White | Program |
| Pin 4 | Yellow | Data - |
| Pin 5 | Black | GND |

¹Removing the waterstop will void the warranty.

²600mm cable length is standard. Custom length is available on request.

³When opting for M12 connector the cable including connector is 300mm.

Product References

DiGi Neonflex

| Reference | Description |
|-----------|--|
| 3171760 | DiGi Neonflex Side Bend 1121 48V RGBW2700K DMX |
| 3171761 | DiGi Neonflex Side Bend 1121 48V RGBW3000K DMX |
| 3171762 | DiGi Neonflex Side Bend 1121 48V RGBW4000K DMX |
| 3171763 | DiGi Neonflex Side Bend 1121 48V RGBW5000K DMX |
| 3171764 | DiGi Neonflex Side Bend 1616 48V RGBW2700K DMX |
| 3171765 | DiGi Neonflex Side Bend 1616 48V RGBW3000K DMX |
| 3171766 | DiGi Neonflex Side Bend 1616 48V RGBW4000K DMX |
| 3171767 | DiGi Neonflex Side Bend 1616 48V RGBW5000K DMX |
| 3171768 | DiGi Neonflex Side Bend 1128 48V RGBW2700K DMX |
| 3171769 | DiGi Neonflex Side Bend 1128 48V RGBW3000K DMX |
| 3171770 | DiGi Neonflex Side Bend 1128 48V RGBW4000K DMX |
| 3171771 | DiGi Neonflex Side Bend 1128 48V RGBW5000K DMX |
| 3171772 | DiGi Neonflex Side Bend 2222 48V RGBW2700K DMX |
| 3171773 | DiGi Neonflex Side Bend 2222 48V RGBW3000K DMX |
| 3171774 | DiGi Neonflex Side Bend 2222 48V RGBW4000K DMX |
| 3171775 | DiGi Neonflex Side Bend 2222 48V RGBW5000K DMX |

Accessories

Straight Profiles

| Reference | Description |
|-----------|---|
| 3167905 | Neonflex 1121/1128 Straight Profile 1000 |
| 3167929 | Neonflex 1121/1128 Straight Profile 2000 |
| 3167939 | Neonflex 1121/1128 Clip Profile |
| 3167964 | Neonflex 1121/1128 Straight Profile Cable Duct 1000 |
| 3167965 | Neonflex 1121/1128 Straight Profile Cable Duct 2000 |
| 3167966 | Neonflex 1121/1128 Straight Profile Transparent |
| 3167904 | Neonflex 1616 Straight Profile 1000 |
| 3167926 | Neonflex 1616 Straight Profile 2000 |
| 3167934 | Neonflex 1616 Clip Profile |
| 3167967 | Neonflex 1616 Straight Profile Cable Duct 1000 |
| 3167968 | Neonflex 1616 Straight Profile Cable Duct 2000 |
| 3167909 | Neonflex 1616 Straight Profile Recessed 1000 |
| 3167913 | Neonflex 1616 Straight Profile Recessed 2000 |
| 3167960 | Neonflex 1616 Recessed Profile End Cap 2pcs |
| 3167969 | Neonflex 1616/1717 Straight Profile Transparent |
| 3167970 | Neonflex 2222 Straight Profile 1000 |
| 3167971 | Neonflex 2222 Straight Profile 2000 |
| 3167972 | Neonflex 2222 Clip Profile |
| 3167973 | Neonflex 2222 Straight Profile Cable Duct 1000 |
| 3167974 | Neonflex 2222 Straight Profile Cable Duct 2000 |

Curved Profiles

| Reference | Description |
|-----------|---|
| 3167919 | DiGi Neonflex Side Bend 1121/1128 Curved Profile 1000 |
| 3167946 | DiGi Neonflex Side Bend 1121/1128 Curved Profile 2000 |
| 3167917 | DiGi Neonflex Side Bend 1616 Curved Profile 1000 |
| 3167931 | DiGi Neonflex Side Bend 1616 Curved Profile 2000 |
| 3167955 | DiGi Neonflex Side Bend 1616 Curved Profile Cable Duct 1000 |
| 3167956 | DiGi Neonflex Side Bend 1616 Curved Profile Cable Duct 2000 |
| 3167957 | DiGi Neonflex Side Bend 2222 Curved Profile 1000 |
| 3167980 | DiGi Neonflex Side Bend 2222 Curved Profile 2000 |