

The Linear Soft Line offers a sophisticated solution for revealing textural elements in premium spaces. Its distinctive soft optic creates smooth illumination that highlights architectural surfaces with elegance and precision, eliminating harsh shadows and hotspots that compromise design integrity.

Perfect for grazing stone facades, textured walls, and surfaces in high-end hospitality, luxury retail, and premium residential environments. This versatile fixture delivers refined, controlled lighting that showcases textures exactly as intended while enhancing rather than overwhelming architectural features.

- ↳ Distinctive soft optic technology – Creates exceptionally smooth, even illumination without harsh shadows or hotspots
- ↳ Premium texture highlighting – Specifically designed to reveal and enhance architectural surface details with precision



CE RoHS IP67 IK08

Specifications

General	
Power Consumption (W/m)	24
Input Voltage (V DC)	24
LEDs (/m)	80
LED Pitch (mm)	12,5
Pixels (/m)	2
Flicker Frequency (kHz)	0,97
LED Type	4in1
Channels (/m)	8
Color Range	RGBW
Optic (°)	12x66
CRI	≥80 (Custom on Request)
Control	DMX
Dimming	16 bit

Installation Conditions & Lighting Data		
Maximum Run Length Power ¹ (m)	6	
Maximum Run Length Data ¹ (m)	@45fps	64
Delivered Lumen Full RGBW (lm)		
Lumen Maintenance Calculated Hours (h)	L80B10	50,000

¹ More details can be found in the Installation Guide document.

Operating	
Environment	Outdoor
Storage Temperature (°C)	-30 to +70
Working Temperature (°C)	-25 to +65
Saltwater Resistant	Yes
UV Resistant	Yes
Flame Resistant	Yes
IK Rating	IK08
IP Rating	IP67
Certification	CE, RoHS
Warranty	3 Years

Physical	
Housing Material	Aluminum (AA6063)
Connector Material	Nylon (PA66)
Cover Material	Tempered Glass
Housing Color	Grey RAL9023 (Custom on Request)
Cable Color	Black
Connector Type	M12 5Pin
Weight (kg/m)	1,4
Dimensions WxH (mm)	65 x 55
Length (mm)	500 / 1000

Options

Color/CCT
<input type="checkbox"/> RGBW2700K
<input type="checkbox"/> RGBW3000K
<input type="checkbox"/> RGBW4000K
<input type="checkbox"/> RGBW5000K

Length
<input type="checkbox"/> 500 mm
<input type="checkbox"/> 1000 mm

Accessories
<input type="checkbox"/> Glare Shield


Lighting Specifications

Linear Soft Line

	Full RGBW (lm/m)	Red (lm/m)	Green (lm/m)	Blue (lm/m)	White (lm/m)
RGBW2700K 12°x66° 500					
RGBW2700K 12°x66° 1000					
RGBW3000K 12°x66° 500					
RGBW3000K 12°x66° 1000					
RGBW4000K 12°x66° 500					
RGBW4000K 12°x66° 1000					
RGBW5000K 12°x66° 500					
RGBW5000K 12°x66° 1000					


Photometric Distribution

Dimensions



¹The dimensions shown are not to scale. Please refer to the Dimensions Sheet document for additional dimensions.

Connection



Connector Pin

Pin 1	Red	24 V+
Pin 2	Green	Data +
Pin 3	White	Program
Pin 4	Yellow	Data -
Pin 5	Black	GND

Product References

Linear Soft Line

Reference	Description
3452746	Linear Soft Line RGBW2700K 12°x66° 500
3452750	Linear Soft Line RGBW2700K 12°x66° 1000
3452747	Linear Soft Line RGBW3000K 12°x66° 500
3452751	Linear Soft Line RGBW3000K 12°x66° 1000
3452748	Linear Soft Line RGBW4000K 12°x66° 500
3452752	Linear Soft Line RGBW4000K 12°x66° 1000
3452749	Linear Soft Line RGBW5000K 12°x66° 500
3452753	Linear Soft Line RGBW5000K 12°x66° 1000